



196 Paterson Ave, 2<sup>nd</sup> Floor  
East Rutherford, NJ 07073  
Tel: 201-299-4499 Fax: 201-335-5909

*"Your #1 Source for Chemical Foaming Agents"*

## **Foamazol™ 10** Chemical Foaming Agent

## **PRODUCT DATA**

### **Application**

Recommended for low temperature applications where high gas yields are desirable.

Characteristics:

Endothermic Decomposition

Regulatory Status:

All Raw Materials Are GRAS (generally regarded as safe)

Physical Appearance:

Supplied as white powder

### **Technical Data**

Decomposition Range:

100-150°C (212-302°F)

Processing Recommendations:

Maximum gas yields are achieved when processing temperatures reach 135-150°C (275-302°F)

### **Usage Levels**

Injection Molding:

0.2-0.75%

Extrusion:

0.2-1.0%

Rotational Molding:

0.5-1.0%

The information and recommendations made herein are based on the research of others and are believed to be accurate. However, nothing herein is to be taken as a warranty, expressed or implied, regarding the accuracy of the information or the use of this product, and purchasers should make their own tests and evaluation to determine the suitability of this product in their application. Nothing herein is to be construed as a recommendation to use or as a license to operate under or to infringe any existing patents.