

196 Paterson Ave, 2nd Floor East Rutherford, NJ 07073 Tel: 201-299-4499 Fax: 201-335-5909

"Your #1 Source for Chemical Foaming Agents"

FoamazolTM 84 Chemical Foaming Agent

PRODUCT DATA

FoamazolTM 84 is a free flowing powder designed for use in **Application**PVC applications. This product combines the benefits of both

PVC applications. This product combines the benefits of both

endothermic and exothermic CFA's to produce controlled gas

yields and obtain uniform cell structures.

Characteristics: Endo/Exothermic Decomposition

Regulatory Status: All raw materials are GRAS (generally recognized as safe)

Physical Appearance: Supplied as a light yellow powder

Technical Data

Decomposition Begins around 150°C (302°F)

Processing Recommendations: Maximum gas yields obtained at 180-190°C (356-374°F)

Usage Levels

Injection Molding: Typical dosages in the range of 0.25-0.75%

Extrusion: Typical dosages are in the range of 0.25-0.75%

The information and recommendations made herein are based on the research of others and are believed to be accurate. However, nothing herein is to be taken as a warranty, expressed or implied, regarding the accuracy of the information or the use of this product, and purchasers should make their own tests and evaluation to determine the suitability of this product in their application. Nothing herein is to be construed as a recommendation to use or as a license to operate under or to infringe any existing patents.